



INTERACTIVE FLAT PANEL



HT65AIO/TS-A06



**WIRELESS
SCREEN SHARE**



**SMART
WHITE BOARD**



**WEB
CONFERENCE**



**MULTI OS
SYSTEM**
(Optional)



4K HDR



**MULTI
TOUCH**

PRODUCT ASPECTS

DISPLAY

Diagonal size	65"
Type of panel	ADS
Backlight type	D LED
Display area	1428.48 (H) x 803.52 (V) mm
Display ratio	16:9
Picture quality	4K HDR
Screen color	1.07 B (10-bit)
Contrast ratio	1200:1
Resolution	3840 x 2160
Pixel pitch	0.372 (H) x 0.372 (W)
Brightness (cd / m2)	350 cd / m2(nits)
Viewing angle	178° (V) / 178° (H)
Refresh rate	60 Hz
Response	5 ms to 8 ms
Panel brand	BOE / LG

TOUCH SCREEN

Touch technology	IR touch
Touch points	20 touch points
Touch accuracy	± 2 mm
Touch resolution	32767 (W) x 32767 (D)
Writing height	≤ 3 ms
Response time	≤10 ms
Drive mode	USB drive free
Interaction methods	Stylus
Surface material	4 mm anti-glare tempered glass (7 Mohs)

SYSTEM

CPU	Quad Core Cortex-A55
GPU	Mali-G52 MP2
RAM	4/8 GB DDR4
Internal storage	32/64/128 GB
OS	Android 11/13

SOFTWARES

System	White board, Screen share, Google Play Store
Third party	WPS Office

CONNECTIVITY

Bluetooth	Version 5.0, frequency 2.4 GHz, distance upto 10 meter
Wi-Fi	Version 802.11 ac/b/g/n/ax, frequency 2.4 GHz + 5 GHz, distance upto 10 meter

INTERFACES

Front panel	USB 3.0 x 2, HDMI IN x 1 , Touch USB 2.0 x 1, Type C x 1, 2 x 15 W speakers (sound track 2.0)
Side panel	RS 232 x 1, Touch USB 2.0 x 1, USB 2.0 x 1, USB 3.0 x 2, HDMI input x 2, RJ45 x 1 (Gigabit ethernet port), RJ45 Out x 1
Bottom panel	Audio input x 1, Audio output x 1

MEDIA FORMATS

Audio	MP3, MAV, WMA, AAC, AC3, EAV3, VORBIS, FLAC, APE, TRUEHD, DTS, DTSHD
Video	H263, H264, H265, MPEG, MPEG2, MPEG4, VC1, VP6, VP8, VP9, AVS, AVS+, AVS2 etc.
Image	JPEG, JPG, PNG, GIF, BMP

POWER CONSUMPTION

Power input	AC 100 V - 240 V / 50-60 Hz
Stand by	≤0.5 W
Total power	≤180 W

OTHERS

Appearance	Case - Aluminium profile side frame + Tempered glass + Cold rolled steel plate Color - Gun metal / Silver + Black
Package	Bare metal size - 1630 x 1050 x 220 mm (L x H x W) Package size - 1645.5 x 230 x 1062.5 mm (L x W x H) Net weight - ≤ 38 KG (without wall bracket) Gross weight - ≤ 48 KG (without wall bracket)
Installation method	Wall mounted and mobile stand (optional)
VESA hole specification	600 x 400 mm
Wall mounting screw	M8 x 25 mm

ENVIRONMENTAL FACTORS

Working temperature	0-40° C
Working humidity	10% RH ~ 90% RH
Storage temperature	-20 ~ +60 C °
Storage humidity	10% RH ~ 90% RH
Working lifetime	≥ 50000 hrs

ACCESSORIES

Obligatory	Dual-head stylus x 2, Remote x 1, Power cable x 1, Wi-Fi Module x 1, Wall bracket x 1
Optional	Floor stand, OPS, USB camera

