



# INTERACTIVE FLAT PANEL



HT75AIO/TS-A06



**WIRELESS  
SCREEN SHARE**



**SMART  
WHITE BOARD**




**WEB  
CONFERENCE**



**MULTI OS  
SYSTEM**  
(Optional)



**4K HDR**



**MULTI  
TOUCH**

# PRODUCT ASPECTS

## DISPLAY

Diagonal size	75"
Type of pannel	ADS
Backlight type	D LED
Display area	1649.66 (H) x 927.97 (V) mm
Display ratio	16:9
Picture quality	4K HDR
Screen color	1.07 B (10-bit)
Contrast ratio	1200:1
Resolution	3840 x 2160
Pixel pitch	0.372 (H) x 0.372 (W)
Brightness (cd / m2)	350 cd / m2(nits)
Viewing angle	178° (V) / 178° (H)
Refresh rate	60 Hz
Response	5 ms to 8 ms
Panel brand	BOE / LG

## TOUCH SCREEN

Touch technology	IR touch
Touch points	20 touch points
Touch accuracy	± 2 mm
Touch resolution	32767 (W) x 32767 (D)
Writing height	≤ 3 ms
Response time	≤10 ms
Drive mode	USB drive free
Interaction methods	Stylus
Surface material	4 mm anti-glare tempered glass (7 Mohs)

## SYSTEM

<b>CPU</b>	Quad Core Cortex-A55
<b>GPU</b>	Mali-G52 MP2
<b>RAM</b>	4/8 GB DDR4
<b>Internal storage</b>	32/64/128 GB
<b>OS</b>	Android 11/13

## SOFTWARES

<b>System</b>	White board, Screen share, Google Play Store
<b>Third party</b>	WPS Office

## CONNECTIVITY

<b>Bluetooth</b>	Version 5.0, frequency 2.4 GHz, distance upto 10 meter
<b>Wi-Fi</b>	Version 802.11 ac/b/g/n/ax, frequency 2.4 GHz + 5 GHz, distance upto 10 meter

## INTERFACES

<b>Front panel</b>	USB 3.0 x 2, HDMI IN x 1 , Touch USB 2.0 x 1, Type C x 1, 2 x 15 W speakers (sound track 2.0)
<b>Side panel</b>	RS 232 x 1, Touch USB 2.0 x 1, USB 2.0 x 1, USB 3.0 x 2, HDMI input x 2, RJ45 x 1 (Gigabit ethernet port), RJ45 Out x 1
<b>Bottom panel</b>	Audio input x 1, Audio output x 1

## MEDIA FORMATS

<b>Audio</b>	MP3, MAV, WMA, AAC, AC3, EAV3, VORBIS, FLAC, APE, TRUEHD, DTS, DTSHD
<b>Video</b>	H263, H264, H265, MPEG, MPEG2, MPEG4, VC1, VP6, VP8, VP9, AVS, AVS+, AVS2 etc.
<b>Image</b>	JPEG, JPG, PNG, GIF, BMP

## POWER CONSUMPTION

<b>Power input</b>	AC 100 V - 240 V / 50-60 Hz
<b>Stand by</b>	≤0.5 W
<b>Total power</b>	≤280 W

## OTHERS

<b>Appearance</b>	Case - Aluminium profile side frame + Tempered glass + Cold rolled steel plate Color - Gun metal / Silver + Black
<b>Package</b>	Bare metal size - 1860 x 1160 x 220 mm (L x H x W) Package size -1868 x 1187.5 x 230 mm (L x W x H) Net weight - ≤ 52 KG (without wall bracket) Gross weight - ≤68 KG (without wall bracket)
<b>Installation method</b>	Wall mounted and mobile stand (optional)
<b>VESA hole specification</b>	800 x 400 mm
<b>Wall mounting screw</b>	M8 x 25 mm

## ENVIRONMENTAL FACTORS

<b>Working temperature</b>	0-40° C
<b>Working humidity</b>	10% RH ~ 90% RH
<b>Storage temperature</b>	-20 ~ +60° C
<b>Storage humidity</b>	10% RH ~ 90% RH
<b>Working lifetime</b>	≥ 50000 hrs

## ACCESSORIES

<b>Obligatory</b>	Dual-head stylus x 2, Remote x 1, Power cable x 1, Wi-Fi antenna x 3, Wall bracket x 1
<b>Optional</b>	Floor stand, OPS, USB camera

